

10/563224

IAP15 Rec'd PCT/PTO 23 JAN 2006

Express Mail No. EV769899313US

PATENT APPLICATION OF

ZHENGFU HAN
TAO ZHANG
GUANGCAN GUO

ENTITLED

AN ADDRESSING METHOD OF QUANTA NETWORK AND
QUANTA NETWORK ROUTER

Docket No. U24.12-0002

AN ADDRESSING METHOD OF QUANTA NETWORK AND QUANTA NETWORK ROUTER

5 BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to an addressing method and apparatus which can be used for network communication via light transmission technology, and more particularly relates to an addressing method and apparatus for quantum information, including quantum communication and quantum computation network system.

2. Description of the Related Art

Quantum information technology is a new scientific field which starts in 1990s. There are many problems being researched, and it is not applied on a large scale, so there will not be any open technologies relate to this invention. According to the experience about classical network information technology, quantum network information technology will be the kernel technology of quantum communication. Comparing with classical communication and considering the characteristics of quantum communication, quantum network system must satisfy these basic capability requirements:

1. multi-user

More than two users can exchange information and share resource at the same time.

25 2. extensibility

The number of users can increase and should not be limited theoretically.

3. independence of the users

This should include two parts: first, the existence and movement of any user only affect those users who exchange information with this user, not the whole network; second, the movement of any user should not be affected by other users except for the one who exchange information with this user, namely crosstalk.

4. Any user in the network should have one and only address or internal serial number (e.g. IP address in classical network), with this address, user can easily distinguish and connect to the user he want to communicate with, the user who is connected can also make sure which user he is talking to.

Special requirements of quantum network:

5. Network system should keep quantum coherence (except receiving and measurement), that means decoherence process should be as weak as possible, and system should not have any photoelectric or electrooptic conversion process except for receiving and measurement.

6. There should not be any amplification of quantum signal inside the network system.
This is the basic requirement of quantum no-cloning theorem.

5 Up to now, there are no quantum network framework theory and technology accord with all the requirements above. The research on quantum key distribution over network has made the biggest progress in this field; existing main technologies come down to:

1. tree topology network

10 This network has two working modes. One mode is, sending modulated single photons to multiple receivers randomly by fibered beam splitters, and then making quantum key distribution between sender and receivers. This mode needs a control center, all users have to share information with control center, that would be unendurable in secure communication sometimes, and besides, communication efficiency is in inverse ratio to the
15 number of terminals in the network and descends when communication distance increases, that limits the extensibility of the network. The other mode uses wavelength addressing, that is, control center uses wavelength as address of receiver, makes quantum key distribution with any user. This mode solves the problem that communication efficiency descends because of the beam splitters, but the security problem, sharing information with
20 control center, still exists. Another important problem is, users besides center can not communicate directly with each other, so tree topology network is not a network proper.

2. ring topology network

25 This network links all users one by one to make one or more closed ring, any two users in the ring make secure communication by certain protocol with the help of control center and do not share any secure information with the center. In this network, all users must be in the ring, which limits the location of the user; the average communication distance between any two users is less than half of the ultimate quantum key distribution distance, and the more users it has, the smaller distance there will be between the adjacent users. This network has
30 already got three modes, first one link each user in series; improved one uses "space optical switch" to link many small rings to a big ring, every user can be on/off the big ring by using "space optical switch", this can achieve variable area quantum network, but in any case, there is only one pair of users can work at the same time; the third one use wavelength addressing, theoretically users can communicate with each other directly without center and
35 work at the same time, but the limitation of the communication distance still exists, the number of wavelength must satisfy $N = n(n-1)/2$, here N is the number of wavelength, n is the number of users, this limits the number of users in the network.

3. multi-particles entanglement network

40 This network can achieve quantum state transmission between multi-users, and is not only a quantum key distribution network, but also a generalized quantum information network. The problem is, the number of entangled particles has minus exponential relationship with product efficiency, and the number of users relates to the number of entangled particles directly, so the number of users is small, expansibility of the network is bad.

In a word, there is no network satisfy the basic requirements of quantum network at present.

SUMMARY OF THE INVENTION

5 It is an object of the present invention to provide an addressing method of quantum network and a quantum network router. With this router, we can construct an equi-weighted multi-user quantum network system.

The network includes at least three nodes, and the method comprises steps of: appointing each node an address serial number; sending photon signals having different wavelengths
10 from each node to other nodes, wherein each of the photon signals regards signal source wavelength and node address as an addressing badge, said addressing badge is made up of two parts, one part is determined by the wavelength of the photon signal which the node sends, the other part is determined by the address serial number of the node; and determining, by each node, where the photon signals come from by using the addressing
15 badges of the photon signals.

When the number of nodes in the network is odd, the number of said signal source wavelength is N; when the number of nodes is even, the number of said signal source wavelength is N-1; here N is the number of nodes in the network.

Said photon signal is optical quantum state signal, or classical optical signal.

20 This addressing method can transmit photon signals having different wavelengths from any node in the network to appointed other node, this kind of transmission is one and only in the network, transmission direction is reversible, that means any node can transmit and receive photon signal, sender beforehand knows where the photon signal having certain wavelength is sent to, receiver knows where the photon signal he receives comes from by measuring the
25 wavelength of the photon signal. Said network can have unlimited amount of nodes.

Said photon signal can be classical signal, e.g. optical pulse comprising lots of photons, it can also be quantum signal, e.g. single photon or entangled photons; said wavelength means a wavelength interval. When the signal is classical signal, the communication process is classical communication, when the signal is optical quantum state, the communication
30 process is quantum communication.

This invention provides a quantum network router to implement said addressing method, it includes a photon signal allocator, the photon signal allocator includes N sets of optical component, here N is the number of nodes in the network, one end of every optical component is mix-wavelength interface, the other end includes separate wavelength
35 interfaces; and an external interface comprising mix-wavelength interfaces of optical components, wherein the number of separate wavelength interfaces is at least N-1, every separate wavelength interface transmits different photon signals having different wavelengths, separate wavelength interfaces of different optical components, which transmit the same wavelength signals, connect one to one.

40 When N is even, said separate wavelength interfaces of optical components are the same, the total number of wavelength used in the whole quantum network router is N-1; when N is odd, any two optical components have one different separate wavelength interface, the total number of wavelength used in the whole quantum network router is N. For example, considered about a router of four optical components, said optical components are the same,
45 each one has three separate wavelength interfaces, i.e. λ_1 , λ_2 , λ_3 , the total number of

wavelength used in the router is three; for router of three optical components, each component has two separate wavelength interfaces, but they are not the same, i.e. No.1 component has λ_1 and λ_2 , No.2 has λ_2 and λ_3 , No.3 has λ_3 and λ_1 , the total number of wavelength used in the router is three too.

- 5 Said optical component can be made up of integrated or separate dispersive and accessorial passive optical components.

Said optical component can be reversible wavelength division multiplexer.

Said optical connection can be achieved via fiber, wave-guide, free space or other optical medium.

- 10 Said optical connection can add collimating, coupling or reflecting optical passive components in the optical path to improve the optical capability of the connection.

Said optical components of the whole quantum network router, include dispersive, collimating, orienting or coupling components, can be integrated with wave-guide substrate totally or partially.

- 15 The internal connections of the quantum network router accord with edge coloring theorem of a graph, any router can be constructed according to this theorem. The correspondence principle is: vertex in edge coloring theorem corresponds to optical component in quantum network router; color corresponds to wavelength (i.e. separate wavelength interface in said optical component). In fact, we can look a quantum network router with odd nodes N as a
20 router with nodes $N+1$, which have one node free or not connected.

Said photon signal can be transmitted from one node to another, reverse transmission is also allowed.

- 25 Said reversible wavelength division multiplexer comprises dispersive part, front/back collimating part and input/output coupler, wherein dispersive part can be filter, raster or dispersive prism.

- The quantum network router of this invention can achieve: receiving photon signals having different wavelengths from all nodes in the network, transmitting the photon signals having different wavelengths which have same aim to their destination by division and coupling, these photon signals can finally be transmitted to certain user by arterial fiber. The working
30 mode of this router won't destroy the quantum state and its coherence, there is not crosstalk either, every path is exclusive, no path superposition or signal loss, user can know where the signal comes from by simply measurement. All above satisfy the basic requirement of network.

- 35 Said all functions correspond to path choosing function in classical communication network or addressing function in computer network. The number of nodes in this quantum network router is unlimited theoretically. With this router and arterial fiber, we can construct a complete quantum network system.

- 40 The addressing method and quantum network router in this invention, regard sender's address and wavelength of quantum state as addressing badge, provides an apparatus of quantum network according to said addressing method, can satisfy the basic requirements of quantum network.

Quantum communication with this invention has many advantages as follows:

- 45 1. Take the router as exchanging and routing center of quantum network, the structure of network is independent from users, so quantum network is similar to classical network, the system composition and operation can be separated and manage canonically.

2. The number of nodes in the router can increase. The total number of wavelength that the router uses is less than the number of nodes, the utilization efficiency of wave band is high, theoretically the wave band can be divided into any shares and utilize repeatedly, the amount of nodes can increase unlimitedly. According to current technology, the amount of nodes can be more than 150, is 3 times bigger than other method.
3. Nodes communicate with different wavelength, channels are separated from each other, isolation of channels only depends on isolation of wavelength division multiplexer, there is little crosstalk and no contention of resource between channels, communication efficiency is impervious to the amount of nodes.
4. Router of this invention has low insertion loss, less than 2dB for each channel.
5. Using this invention can realize quanta communication in deed, includes quanta cryptographic key distribution, quanta network transmission, namely generalized quanta communication, composing quanta computer addressing bus or quantum computer network, etc.
6. Because quantum network comes from classical network appending some limitation, this quantum network router can be optical router in classical communication, realize static routing function in classical communication network.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of internal structure of 4 nodes quantum network router which is made up of commercial wavelength division multiplexers.

FIG. 2 is a block diagram of internal structure of 3 nodes quantum network router which is made up of commercial wavelength division multiplexers.

FIG. 3 is a block diagram of internal structure of 4 nodes quantum network router which is made up of separate components.

FIG. 4 is a block diagram of internal structure of integrated 4 nodes quantum network router.

FIG. 5 is a form of IP address of 3 nodes quantum network router.

FIG. 6 is a form of IP address of 4 nodes quantum network router.

DETAILED DESCRIPTION OF THE INVENTION

structure of quantum network router

1. quantum network router which is made up of commercial wavelength division multiplexers

Quantum network router can be made up of commercial wavelength division multiplexers according to the principle of the invention. FIG. 1 shows a typically block diagram of internal structure of 4 nodes quantum network router. As shown in FIG.1, inside dashed is

the internal structure of router, 1-1~1-4 are the same commercial wavelength division multiplexers, λ_1 , λ_2 , λ_3 are different wavelengths (in fact it is wave band of certain width) which should satisfy the requirement of insertion loss and isolation; 2-1~2-6 are connections between separate wavelength interfaces which have the same wavelength, they can be optical paths comprising single mode fiber, separate component or wave-guide; 3-1~3-4 are mix-wavelength interfaces, and can be connected with users by arterial fiber.

FIG.2 shows internal structure of three nodes quantum network router, wherein 4-1~4-3 are wavelength division multiplexers, the difference from four nodes router is, every multiplexer has different wavelengths, 4-1 has λ_1 and λ_2 , 4-2 has λ_2 and λ_3 , 4-3 has λ_3 and λ_1 , the total number of wavelength is three. 5-1~5-3 are connections between separate wavelength interfaces which have the same wavelength, they can be optical paths comprising single mode fiber, separate component or wave-guide; 6-1~6-3 are mix-wavelength interfaces, and can be connected with users by arterial fiber. In fact, this three nodes router can be looked as a special four nodes router in FIG.1 with one node and all connections with it disappeared.

If put multiplexer 1-2 and connections 2-2 2-5 2-6 in FIG.1 away, four nodes router in FIG.1 will become three nodes router in FIG.2. Similarly, any router with even nodes N can become N-1 nodes router by putting one node away.

Any N nodes router can be constructed with multiplexers according to principle above described, router with odd nodes is similar to FIG.2, and router with even nodes is similar to FIG.1.

2. 4 nodes quantum network router which is made up of separate components

Quantum network router can be made up of separate passive optical components instead of making wavelength division multiplexer first and then constructing quantum network router. This kind of router with N nodes can be made up of N dispersive components and accessorial orienting parts, e.g. collimating, coupling or reflecting optical passive components, prism or other refracting device.

FIG.3 shows the internal structure of four nodes quantum network router which is made up of separate components. 7-1~7-4 are dispersive components and can achieve splitting and coupling of signal, they can be prism, filter or raster. 8-1~8-4 and 9-1~9-4 are front/back collimating system; its function is collimating and focalizing of ray. 10-1~10-4 are orienting components, its function is orienting ray to certain dispersive component; 11-1~11-4 input/output couplers; they connect with users by arterial fiber.

3. integrated quantum network router

Quantum network router can be made up of integrated optical components. N nodes router can be made up of N integrated dispersive components and orienting wave-guide.

FIG.4 shows four nodes integrated quantum network router. 12-1~12-4 are integrated raster, their function is, separate mix-wavelength signal to single wavelength signals or reverse; 13-1~13-6 are wave-guide for single wavelength signal, transmit the signal to raster; 14-1~14-4 are mix-wavelength interfaces, they connect with users by arterial fiber.

When a quantum network router is finished, every node has a form of IP address, the user connect with this node can find the address of other users according to the form and

FP050059

communicate with them. FIG.5 and FIG.6 show the forms of IP address for three nodes and four nodes quantum network router. For router with more than four nodes, there is also a form of IP address, form for odd nodes router is similar to FIG.5, form for even nodes router is similar to FIG.6.